

DUAL MONO  
REFERENCE  
PREAMPLIFIER

# EC 4.8



## TECHNICAL SPECIFICATIONS

- **Input impedance:** 47 kOhm
- **Input level:** Single ended > 15 Vp-p /  
Balanced > 30 Vp-p
- **Noise floor:** (20 - 20 kHz) < -130 dB
- **Channel separation:** (20 - 20kHz) > 120 dB
- **Frequency response:** 0.5 - 200 kHz
- **Gain:** -111dB to +6dB
- **Output impedance:** 100 Ohms
- **Output level:** Single ended > 15 Vp-p /  
Balanced > 30 Vp-p
- **THD :** (1Vin, 1Vout, 1kHz) < 0,002%.
- **Power consumption:** (no load or signal) 30 W
- **Dimensions:**  
Width: 483 mm - 19"  
Depth: 368 mm - 14.5"  
Height: 76 mm - 3"
- **Weight:** 9 kg - 19.8 lbs

With its outstanding performance, excellent resolution, superb control and precise musical reproduction, we have finally succeeded in making a preamplifier that is true to our slogan, "Closing the gap to the master". Our new two-channel EC 4.8 preamplifier is sure to make all good power amplifiers sound even better!

The EC 4.8 preamplifier is designed to fill our need for a advanced preamplifier. The preamplifier is a stylish slim-line design and offers fully balanced operation from input to output. It is designed as two separate mono preamplifiers, each with its own independent power supply. This preamplifier can be used with the included IR remote controller or, as an option, with the RF based remote controller ECT 3. The EC 4.8 includes the innovative SPAC network technology that provides safety for connected power amplifiers.

