

BALANCED DAC
192KHZ/24 BIT

ECD 2



The new ECD 2 combines the classic Electrocompaniet design with modern technology. The sound from any digital source like Blu-ray, CD players, TV/ Satellite tuners, computers and iPod docking stations will be improved. Digital sources can be connected by 2 x Coax, Toslink and USB inputs. The USB port is asynchronous and supports 24 bit / 192 kHz resolution.

The selected source and volume is shown on the large easy to read display, and all functions are easily controlled by the remote control. For output the ECD 2 offers both balanced (XLR) and single-ended (RCA).

As an option the EMT 1 Music Transmitter and EMR 1 Music Receiver can be connected offering wireless transmission of audio from your computer.



TECHNICAL SPECIFICATIONS

- Number of channels: 2ch
- Output Impedance: 300 Ohms
- Output level (Balanced) : 4.6 Vrms
- Output level (Single-ended): 2.3 Vrms
- Noise floor (20 - 20 kHz): < -145 dB
- Frequency response: 0.5 - 48 kHz
- THD+N: < 0,0005 %
- Upsampling rate: 192 kHz, 24 bit
- Digital/Analog conversion: 192 kHz, 24 bit

- Input sampling rate:
- SPDIF Coax: 192 kHz, 24 bit
- SPDIF TOSLink: 96 kHz, 24 bit
- USB: 192 kHz, 24 bit asynchronous

Power consumption:

- {no load or signal} 50 W
- standby 0.5 W

Dimensions:

Width 465 mm – 18.3"
Depth 316 mm – 12.4"
Height 78 mm – 3"

- Weight: 8 Kg – 18 lbs